

Model CM712 Temperature and Humidity Monitor

SPECIFICATION SHEET

- ◆ You need to monitor your cooler and freezer, but you don't have an analog phone line.
- ◆ You want to monitor you vacation home, but don't want to pay for the phone line you never use.
- ◆ You want to monitor your R.V. (with your pet inside) while you are out to dinner.
- ◆ **The CM712 is perfect for you.**
- ◆ The CM712 has one internal temperature and humidity sensor
- ◆ You also have the ability to add two external temperature sensors, two door sensors and two water sensors.



User Programmable Features

Up to 4 cell numbers for sms alerts
 Celsius or Fahrenheit
 Upper and lower limits for all sensors with individual delay times
 Ability to name each sensor
 Power outage time delay
 Status update time once a day, you choose the time
 Password protection
 Internal rechargeable batteries
 Works with a Twitter account

Specifications

Temperature Measuring Range	Internal External	32°F to 125°F (0°C to 51°C) 1 deg. resolution -328°F to 392°F (-200°C to 200°C) 1 deg. resolution
Sensor Type	Internal External	Sensirion SHT-71 RTD: 2 wire, 1000 ohm, Platinum, .00385 TCR
Humidity Measuring Range		0 to 100%
Humidity Sensor Accuracy		+/-3% (from 20-80%RH) 1% resolution
Power requirements		12VDC 200mA or 115VAC
Dimensions		5.625" x 3.250" x 1.375"
Cell Module Specification		Quad Band EGSM 850/900/1800/1900MHz PTCRB Certified
SIM		Uses standard sim card (AT&T or T-Mobile in USA)

Model CM712 Temperature and Humidity Monitor

SPECIFICATION SHEET

