

## Model BP2-G Temperature Sensor

### Specification Sheet



- NIST certificates are available and recommended if storing vaccines
- 10' of wire included with each sensor, more available for purchase
- Vials filled with propylene glycol are designed to mimic a vaccine bottle
- For all Temperature Guard Models

#### Description:

The temperature sensors incorporate a Class A, Thin Film Platinum RTD sensor which conforms to DIN-IEC-751 platinum RTD standards. These sensors are available in two or three wire configurations, incorporating high accuracy and interchangeability throughout a wide operating temperature range.

#### Specifications:

Output	1K Ohms @ 32°F (0°C)
Accuracy	+/- 0.06% @ 32°F (0°C) Single Point +/- 1.0 Ohm @ 70°F (Averaging)
Stability	Less than +/- 0.1°C drift
Repeatability	+/- 0.2°C (+/- 0.36°F)
Operating Temperature Range	BP2 -58 to 392°F (-50 to 200°C) BP2-G -58 to 176°F (-50 to 80°C)
Temperature Coefficient	0.00385 Ohm/Ohm/°C
Standardization	DIN-IEC-751 (formerly DIN 43760)
Resistance Characteristics	+/- 0.06% Class A (Standard)
Dimensions	1.25" Diameter X 2.75" Height X 1 oz. Capacity